

COMMUTER

C9287

- Good driving control
- Impressive drainage performance
- Excellent wear resistance



Tire Size	OD	SW	Rim size	PR	TT/TL	Load kg
8 1/2 x 2	230mm	50mm	6.10X1.38	2	TT	75

C9361

- Good driving control
- Impressive drainage performance
- Excellent wear resistance



Tire Size	OD	SW	Rim size	PR	TT/TL	Load kg
8 1/2 x 2	230mm	50mm	6.10X1.38	4	TT	75
230 x 50	230mm	50mm	6.10X1.38	4	TT	75
254 x 54	254mm	54mm	6.60X1.65	4	TL	80
60/70-6.5	254mm	58mm	6.50X1.65	4	TL	80

C9336

- Good driving control
- Impressive drainage performance
- Excellent wear resistance



Tire Size	OD	SW	Rim size	PR	TT/TL	Load kg
10 x 2.50	10"	61mm	6.00X1.04	4	TT	77
11 x 2.50	274mm	60mm	6.50X1.65	4	TT	112

CM531

- Good driving control
- Impressive drainage performance
- Excellent wear resistance



Tire Size	OD	SW	Rim size	PR	TT/TL	Load kg
10 x 2.25	10"	55mm	6.00X1.06	2/4	TT	65
10 x 2.50	10"	63mm	6.00X1.65	4/6	TL	80/100
10 x 2.50-6.5	10"	59mm	6.50X1.65	4	TL	75
10 x 2.70-6.5	250mm	70mm	6.50X1.65	4	TL	75
12 x 3.00-6.5	305mm	85mm	6.50X2.15	4	TL	95
65/80-8 (N)	305mm	64mm	8.00X1.65	4	TL	95

C9368

- Good driving control
- Impressive drainage performance
- Excellent wear resistance



Tire Size	OD	SW	Rim size	PR	TT/TL	Load kg
60/70-6.5	251mm	58mm	6.50X1.65	4	TL	75
9.5 x 2.50	241mm	65mm	6.10X1.70	4	TL	75
9.5 x 2.30	241mm	58mm	6.10X1.70	4	TL	75
10 x 2.30-6.5	252mm	60mm	6.50X1.65	4	TL	75
10.5 x 2.50	265mm	65mm	7.00X1.70	4	TL	80
10 x 2.125	254mm	54mm	6.60X1.60	4	TT/TL	80
10 x 2.50-6.5	254mm	59mm	6.50X1.65	4	TL	75
10 x 2.50-7	262mm	60mm	7.00X1.65	4	TL	75
10.5 x 3.00-7	267mm	76mm	7.00X2.10	4	TL	100

CM560

- Large, flat contact patch for good driving stability
- Excellent wear resistance
- Efficient drainage



Tire Size	OD	SW	Rim size	PR	TT/TL	Load kg
10 x 3.00-6	10"	79mm	6.00X2.15	4	TL	95
9 x 2.50	230mm	64mm	6.00X1.60	4	TL	80

CM595

- Symmetrical groove pattern
- Nylon carcass
- Excellent driving stability



Tire Size	OD	SW	Rim size	PR	TT/TL	Load kg
10 x 2.50-6	249mm	62mm	7X1.65	4	-	PU

C9379

- Quiet ride technology
- All-weather traction
- Optimised road grip



Tire Size	OD	SW	Rim size	PR	TT/TL	Load kg
10 x 2.70-6.5	250mm	64mm	6.50X1.65	4	TL	75



CST®

E-SCOOTER RANGE

E-ROLLER

City E-Roller tires are tailored for urban environments



SPORT – SPEED

C9316 ROLLER

- Large contact patch for good driving stability
- Excellent wear resistance
- Efficient drainage



Tire Size	OD	SW	Rim size	PR	TT/TL	Load kg
90/65-6.5	281mm	93mm	6.50X2.50	4	TL	121

CM580N ROLLER

- Large, flat contact patch for good driving stability
- Excellent wear resistance
- Efficient drainage



Tire Size	OD	SW	Rim size	PR	TT/TL	Load kg
90/55-7	280mm	98mm	7.00X2.60	4	TL	100

ROLLER

AT E-Roller tires excel in all terrains

ROLLER

HS E-Roller tires are built for high-speed performance

SPORT – ALL-TERRAIN

C6559S ROLLER

- Rapid water evacuation
- Minimal rolling resistance
- Off-road durability



Tire Size	OD	SW	Rim size	PR	TT/TL	Load kg
10 x 3.00-6	250mm	83mm	6.50X2.15	4	TT	95
100/55-6.5	280mm	100mm	6.50X2.50	4	TL	145
100/55-7	286mm	100mm	7.00X2.60	4	TL	100

C6017 ROLLER

- Optimised road grip
- Aero-dynamic efficiency
- High-speed stability



Tire Size	OD	SW	Rim size	PR	TT/TL	Load kg
10 x 3.00-6	250mm	83mm	6.00X2.15	4	TL	95
11.5 x 3.50-7	292mm	96mm	7.00X2.60	4	TL	80

C9299S ROLLER

- Off-road durability
- Weight distribution optimisation
- Impact absorption capacity



Tire Size	OD	SW	Rim size	PR	TT/TL	Load kg
80/55-7	267mm	78mm	7X2.28	4	TL	95

C126 ROLLER

- Even block pattern design with bridge connections for stability and wetland grip
- Excellent wear resistance



Tire Size	OD	SW	Rim size	PR	TT/TL	Load kg
12 x 3.00-6.5	305mm	85mm	6.50X2.15	4	TL	95

C858 ROLLER

- Well-arranged block pattern design for good wet grip
- Additional sipes for drainage and driving stability
- Excellent wear resistance



Tire Size	OD	SW	Rim size	PR	TT/TL	Load kg
70/75-6.5	275mm	69mm	6.50X2.00	4	TL	70
90/65-6.5	281mm	83mm	6.50X2.50	4	TT/TL	189

Introducing Defender FullCore Technology:

NO MORE FLATS!

Defender FullCore Technology revolutionises the tire industry by incorporating a unique foam core that completely fills the interior of the tire, ensuring it remains operational at all times.

Zero-Flat Design:

A revolutionary foam interior guarantees that the tire cannot go flat, offering unparalleled reliability and peace of mind.

Puncture Immunity:

The foam core acts as an impenetrable barrier against punctures for continuous functionality.

Unmatched Durability:

Defender FullCore tires deliver superior durability for significantly extended tire life.

Optimal Performance:

Constant internal pressure and structural integrity ensures consistent performance and efficiency.

Enhanced Comfort:

The foam core improves ride comfort by absorbing vibrations and shocks, making for a smoother journey.



A GROUNDBREAKING SOLUTION THAT SURPASSES THE LIMITATIONS OF CONVENTIONAL TIRES

CST