

# TRAILER TYRES

Product range



# TREAD PATTERNS



B13



B14



B61



B62

Code	Tyre size	Load index, speed symbol	Tread pattern designation	TL/TT	Tyre width (mm)	Outer diameter (mm)	Rim	Load (kg)	Inflation pressure (bar)	Max speed (km/h)
573368	3.50-8	46J (4PR)	B13	TT	92	386	2.50	170	2.50	100
573354	4.00-8 C	71J (6PR)	B13	TT	108	415	3.00	345	4.25	100
573356	4.00-8 C	66N (4PR)	B13	TL/TT	108	415	3.00	300	3.50	140
573390	3.50-10	59J REINF.	B14	TT	92	437	2.50	243	3.25	100
573384	4.00-10C	69J (4PR)	B14	TL/TT	108	466	3.00	325	3.50	100
573385	4.00-10C	74J (6PR)	B14	TL/TT	108	466	3.00	375	4.25	100
588217	4.80/4.00-8	70N (6PR)	B61	TL	116	416	2.50	335	5.00	140
588230	4.50-10 M+S	76N (6PR)	B61	TL	134	495	3.50	400	4.25	140
588220	5.00-10 M+S	72N (4PR)	B61	TL	146	522	3.50	355	3.50	140
588231		79N (6PR)		TL		522		437	4.25	140
588182	145-10 M+S	79N (6PR)	B61	TL	146	504	3.50	437	4.25	140
588171	195/50-10 (18x8.0-10)	98N	B62	TL	188	453	6.00	750	6.00	140
588213	195/55-10C	98/96N	B62	TL	208	472	7.00	750/710	6.25	140

Trailers are a great solution when you need to transport bigger and heavy items, and also when you go on holiday and lack space in your car.

When choosing the correct tyres for your trailer, pay attention not only to rim size but also to load and speed index. Inappropriate load and speed index may negatively affect tyre wear and safety. Trailers are usually not in daily use and could be stored for a longer time either outdoors or in a garage. Please check for inflation pressure and any signs of ageing before using your trailer, especially if not in use for some time.

Mitas light trailer tyres will win your trust with their high quality and long service life.

## Mitas Two Wheels & Specialty Tyres

Škofjeloška cesta 6, 4000 Kranj, Slovenia

Phone: +386 4 206 58 83

e-mail: info-moto@mitas-tyres.com

mitas-tyres.com